



MODEL	OUTPUT SIDE			INPUT SIDE			MOUNTING										RATING				
	ØD	H	J	L1	Ød	h	J	L2	C	X	Y	A	B	LF	G	T	M	ØP	S	MAX. POWER	TORQUE KGM
160CR	28	31	8	45	19	21.5	6	30	100	167	120	200	150	280	64	10	12	160	63	2 H.P.	15
200CR	32	35	10	55	24	27	8	40	100	190	120	220	150	326	76	10	12	200	86	5 H.P.	40
250CR	38	41	10	55	28	31	8	45	130	220	170	260	210	362	77	15	14	250	110	10 H.P.	80
300CR	42	45	12	65	28	31	8	45	158	240	200	275	250	386	85	15	14	300	120	20 H.P.	150
400CR	48	51.5	14	90	38	41	10	55	205	245	300	280	350	432	110	18	14	400	126	40 H.P.	250

REDUCTION RATIO - 10:1

VIJAY ENGINEERING WORKS.

DS2/3, ADDITIONAL MIDC, SATARA.

TEL. NO.(02162)240314 (09881732219)

DRN. SLF

CHD.

APPD.

ITEM : G.A. DRAWING CREEP DRIVE

CODE NO. : _____

ALL DIM. ARE IN MM

SCALE : N.T.S.

REMOVE ALL SHARP CORNERS & BURR.

TOLRRANCE FOR OPEN DIM. IS +0.2mm